



STELCO BATTERIES A LIFETIME OF LOW MAINTENANCE

Get more Power with STELCO Low Maintenance Batteries. Every STELCO Low Maintenance Battery is made of a premium alloy composition imported from PASMINCO Australia. This amazingly special high-grade alloy gives STELCO batteries the leading edge. STELCO satisfies the demand for low maintenance. Less frequent top-ups and long life batteries.

WHYALTIMA BATTERIES ARE THE BEST?

Our Automotive range is manufactured on a state of the fully automatic battery assembly line form LEKO U.S.A. advanced Japanese technology is applied while designing our batteries, ensuring optimum performance, extremely long life, reliable and resistance to typically abusive Indian roads and climate.

Technical Specifications

TECHNICAL SPECIFICATIONS AUTOMOTIVE							
Battery Type	АН	Capacity(Ah)		Dimensions(mm)			CHG.
		C20	C 5	Length	Width	Height	AMPS
SB-40E	35AH	35	29	195	127	223	3.5
SB -38B 20L	35AH	35	29	195	127	223	3.5
SB-40LBH	35AH	35	29	195	127	223	3.5
SB-60Z (55B24L)	45AH	45	37	230	127	227	4.5
SB-600	60AH	60	50	257	170	224	4.5
SB-750L	70AH	70	58	257	170	224	7
SB-750R	70AH	70	58	257	170	224	7
SB-800	80AH	80	66	302	170	225	8
SB-950	95AH	95	79	410	170	230	9.5
SB-1100	110AH	110	91	410	170	230	11
SLX-12000	120AH	120	100	510	180	235	12
SLX-15000	150AH	150	125	505	220	255	15
SLX-16000	160AH	160	133	505	220	255	16
SLX-18000	180AH	180	149	505	220	255	18
SB-DIN 44LMF	44AH	44	37	220	175	175	4.4
SB-DIN 50LMF	50AH	50	42	240	175	190	5
SB-DIN 55LMF	55AH	55	46	275	175	175	5.5
SB-DIN 65LMF	65AH	65	54	275	175	175	6.5

Other Advantage of STELCO Batteries include

- 1. Well-designed 'Positive Plates' provide maximum surface area for high power and voltage endurance.
- 2. Special computerized design of the 'Negative Plates' provides perfect balance along with the positive, thus giving maximum performance.
- ${\it 3.} \quad {\it Rugged POLYPROPYLENE} \ containers \ assist in high impact resistance.$
- 4. Advanced glass mat separator protects against active material shedding during bump and vibration assuring high service life.
- 5. Fine pores of polyethylene envelopes separators help in the free electrolyte movement between the positive and the negative plates. This enhances the cold cranking ability of the battery. Problems of internal short-circuits within the cell are also eliminated easily.
- 6. The unique thorough partition, resistance welded inter cell connection, dramatically shortens the power path and minimizes voltage drop on cranking.
- 7. The heavy-duty plate density provides increased plate strength. A special chemical formulation drastically reduces sulphation, allowing full recharging and significantly prolonged battery life.

CORPORATE/REGD. OFFICE:



A NAME TO BE TRUSTED UPON

Sparco Battery Corporation, which was established in the year 1965. Since then, it has emerged as one of the leading manufacturer and exporter of lead-acid batteries across India and globe. With Our 55 years of market experience, hi-tech manufacturing facilities and well defined quality management system, we ensures that every battery leaving the plant is manufactured with quality and highest international standards. Customer satisfaction has been core of all our endeavours. Ever since its foundation, the Company has served well in the markets of Northern, Central and Western parts of India. Apart from Indian markets company has successfully launched its products in Africa, Middle East and SAARC Countries.

VISION

To reach beyond the rules of the conventional companies and create a benchmark in the industry.

MISSION

To surpass the expectations of our customer through our product with innovation. To consistently deliver reliable product at best possible price with excellent after sales service. Through work oriented passionate people we are consistently improving to achieve our goal of becoming a successful producer of 2 million batteries per annum.





CORPORATE/REGD. OFFICE:

A-35/1,Maya Puri Indl.Area,Phase-I,New Delhi-64 Mob: 9911324365 | Tel: +91-011-41579214 E-mail: info@altima.in | Website: www.altima.in